TM

GARLOCK

EQUIPMENT COMPANY

Enforcer



Reduce Downtime

Minimize Cutting time

Increased Jobsite Safety

Maximize Productivity: With the Garlock Enforcer Increase roof tear off productivity by up to 300 Percent when compared to single bladed roof cutters, and boost profitability by cutting up to 70 squares per hour.

Reduce Downtime: Change belts on the roof with the quick change belt design. No need to drop the arbor shaft assembly. Simplify maintenance with the acces panel and on-board wrench storage.

Minimize Cutting Time: Get the cutting done in half the time and get your crews to work sooner vs. single blade cutters. Cut a 25 inch tearoff width for maximum use of trash chute capacity.

Increased Jobsite Safety: With the enforcer all engine and operating controls within easy reach. Press the foot pedal to start the cut and push down on handlebars to stop cutting. Cut at your pace with the variable speed hydrostatic drive.





Operator Control Station

www.profastinc.com

ENFORCER: FEATURES AND OPTIONS



Depress foot pedal to lower saw into cut. Press down on handlebar to raise saw.



Rugged belt drive system with quick access panel.



Tearoff width 25" in one pass.



Standard headlight for extended working hours.



Hour meter for maintaining service intervals.



Extended operation fuel tank.

SPECIFICATIONS

Enforcer Twin Saw

Weight	550 lbs.
Dimensions (LxWxH)	71" × 33" × 40"
HONDA Engine HP	20 hp
Drive System	Hydrostatic transaxle
Blade Guard Design	Dual Floating design
Wheel/ tire design	Dual foam filled
Tearoff cut width	25"





Philadelphia Office

6 Poulson Ave PROFAST P.O. Box 156 Essington, PA 19029 Phone: 610-521-3404

Fax: 610-521-4717 Fax: 717-458-5613

Harrisburg Office

7917 Derry St Suite 106 Harrisburg, PA 17111

Pittsburgh Office

503-5 North Drive Sewickley, PA 15143 Phone: 412-259-8449

Phone: 717-458-5610 Fax: 412-291-3188